

issued as Patent No. 6,143,576, which is a continuation in part of U.S. Patent Application No. 08/447,981, which issued as U.S. Patent No. 5,885,527 on March 23, 1999, which is a divisional application of U.S. Patent Application No. 08/065,528 (abandoned), filed 19 May 1993, which was a continuation-in-part of U.S. Patent Application No. 07/887,526 filed 21 May 1992 which issued as Patent 5,458,852 on October 17, 1995; and U.S. Patent Application No. 08/902,775 which issued U.S. Patent No. 6,271,040, which is a continuation in part of U.S. Patent Application No. 08/810,569 which issued as Patent No. 6,143,576, from each of which priority is claimed, and each of which is fully incorporated by reference herein.

IN THE CLAIMS

Please cancel claims 1-7<sup>3</sup> provided in the original specification and enter the following new claims: These new claims are reflected in the specification filed herewith.

1. A method for regulating fluid flow in a device that conducts fluid through one or more capillary channels, comprising:

introducing fluid into a capillary channel comprising (i) a first capillary region comprising a hydrophilic surface and (ii) a second capillary region comprising a hydrophobic surface adjacent to said first capillary region, whereby fluid flows through said first capillary region to contact said hydrophobic surface.

2. The method of claim 1, wherein said device further comprises a third capillary region comprising a hydrophilic surface adjacent to said second capillary region, wherein said hydrophobic surface controls the rate of flow of said fluid into said third capillary region.

3. The method of claim 2, wherein said hydrophobic surface delays fluid flow into said third capillary region until rendered hydrophilic.

4. The method of claim 1, wherein said device comprises a plurality of capillary channels, one or more of which comprise a region comprising a hydrophobic surface.

5. The method of claim 2, wherein said device further comprises a vent.

A method for regulating fluid flow in a device that conducts fluid through one or more  
 ry channels, comprising:

86. A device that conducts fluid through one or more capillary channels, comprising:

a capillary channel comprising (i) a first capillary region comprising a hydrophilic surface and (ii) a second capillary region comprising a hydrophobic surface adjacent to said first capillary region.

87. The device of claim 86, wherein said device further comprises a third capillary region comprising a hydrophilic surface adjacent to said second capillary region.

88. The device of claim 86, wherein said hydrophobic surface alters a rate or direction of fluid flow within said device.

89. The device of claim 86, further comprising a reagent dried on a surface of the device that, when dissolved into reagent dissolves into fluid within said device, lowers the surface tension of said fluid.

90. The device of claim 86, wherein said device comprises a plurality of capillary channels.

91. A method for regulating fluid flow in a device that conducts fluid through one or more capillary channels, comprising:

introducing fluid into a capillary channel comprising (i) a first capillary region comprising a surface having a first contact angle and (ii) a second capillary region adjacent to said first capillary region comprising a surface having a second contact angle less than that of said first contact angle, whereby fluid flows through said first capillary region to contact said second capillary region.

92. The method of claim 91, wherein said device further comprises a third capillary region adjacent to said second capillary region comprising a surface having a third contact angle greater than that of said second contact angle, wherein the rate of flow of said fluid into said third capillary region is regulated by the flow of fluid through said second capillary region.

93. The method of claim 92, wherein said second capillary region delays fluid flow into said third capillary region until said second contact angle is increased.